



PPG Silica Products

Agilon® Performance Silicas

TIRE

Agilon® Performance Silicas for Tire

Designed to improve the performance and processing of highly dispersible silica (HDS) green tire tread formulations, Agilon® performance silicas support the tire industry's need for safer, more environmentally responsible products by lowering rolling resistance and improving tire handling and traction.

Agilon performance silicas eliminate the need for silane coupling agents, thus increasing manufacturing efficiency and reducing associated volatile organic compound (VOC) emissions.

***Agilon* performance silicas drive top line results through improved tire performance, while streamlining the manufacturing process for bottom line cost savings.**

Benefits

- Enables tire makers to develop new and differentiated technologies
- Improves tire performance (rolling resistance, handling and traction)
- Reduces VOC emissions for a more environmentally responsible manufacturing process
- Increases production efficiencies by eliminating the in-situ silica/silane mixing step
- Enables high temperature mixing without increasing viscosity or causing premature vulcanization
- Eliminates extrusion inefficiencies due to porosity concerns
- Improves shelf life of uncured rubber





Samples

Samples are available per request from customer service.

Packaging

Standard packaging includes small bags and Flexible Intermediate Bulk Containers (FIBCs). Bags are unitized for shipping on pallets which are stretch wrapped with clear plastic film. FIBCs are single or double stacked on wood pallets. Please consult with Silica Customer Service or your Silica Sales Representative regarding additional packaging options including custom package sizes and bulk shipments.

Storage

To ensure product integrity, PPG recommends that our silica products be stored under dry, clean conditions, protected against exposure to direct sunlight and other substances, and used within twelve months of the date of manufacture.

Safety and Health Effects

PPG Industries recommends that, before use, anyone using or handling this product thoroughly read and understand the information and precautions on the label, as well as in other product safety publications such as the Material Safety Data Sheet. Any health hazard and safety information contained herein should be passed on to your customers or employees, as the case may be. The products mentioned herein can be hazardous if not used properly. Like all potentially hazardous materials, this product must be kept out of the reach of children.

Typical Properties

	Agilon 400 Silica	Agilon 454 Silica	Agilon 458 Silica
CTAB Surface Area, m ² /g	140	200	200
N ₂ (BET-5) Surface Area, m ² /g	75	140	115
SH, Wt. %	0.5	0.5	0.5
Carbon, Wt. %	4.0	4.0	6.0
pH	6.5	6.5	6.5
Residual Salt Type	Na ₂ SO ₄	Na ₂ SO ₄	Na ₂ SO ₄
Physical Form	Granule	Granule	Granule

Typical Passenger Tread Performance

	160 CTAB HD Silica/ In-Situ Silane	200 CTAB HD Silica/ In-Situ Silane	Agilon 400 Silica*	Agilon 454 Silica*	Agilon 458 Silica*
Processing	Good	Fair	Best	Good	Better
Dispersibility	Good	Fair	Best	Best	Best
Reinforcing Capability	Good	Better	Good	Better	Better
Stiffness / Handling	Good	Better	Good	Best	Better
Fuel Efficiency	Good	Good	Best	Better	Better
Traction	Good	Good	Best	Better	Better
Treadwear	Good	Better	Good	Better	Better

* Requires appropriate changes in curatives, filler, free oil and zinc oxide loadings as well as mix time and temperatures.

Product Safety and Regulatory Information

For the latest product safety and regulatory information, please reference the Product Safety Sheets at www.ppgsilica.com.



PPG Silica Products

Bringing innovation to the surface.™

USA
PPG Silica Products
440 College Park Drive
Monroeville, PA 15146 USA

Customer Service: 1-800-243-6745
Technical Service: 1-800-764-7369
E-mail: silicacustserv@ppg.com

EUROPE
PPG Industries Chemicals bv
Silica Products
P.O. Box 181
9930 AD Delfzijl, The Netherlands

Customer Service: +31-596-676710
Technical Service: +31-596-676710
E-mail: csdelfzijl@ppg.com

